

RHINO-RACK®

Batwing Compact Awning


33120 (Left) / 33121(Right)

Important:

1. Check the Rhino-Rack website to ensure you have the latest issue of these instructions.
2. Please refer to your fitting instruction to ensure that the roof racks are installed in the correct locations.
3. Check the contents of kit before commencing fitment and report any discrepancies.
4. Place these instructions in the vehicle's glove box after installation is complete.
5. These instructions must be followed for warranty to be upheld.

Fit Time: 15 mins

TWO-PERSON
INSTALLATION



Thank you for choosing Rhino-Rack!












WELCOME TO THE HERD.

For peace of mind register
your product by heading to
rhinorack.com/register

Rhino-Rack AUSTRALIA
22A Hanson Place,
Eastern Creek, NSW 2766

Rhino-Rack USA
19822 E. 22nd Avenue,
Unit B, Aurora, CO 80011

RHINORACK.COM
Document No: 520-RFI-00214
Issue No: 04
Issue Date: 18/06/2025



Important Information

Recommendations

Use only non-stretch fastening ropes or straps.

Please remove Batwing Awning and crossbars when putting vehicle through an automatic car wash.

Do not stow away the awning for long periods if it is wet. You must allow the awning material to dry completely before storing for extended periods of time. When rolling up the awning, avoid excessive bunching up of the material before stowing. The awning should be rolled up as neatly as possible following the instruction on page 9.

In service maintenance checks

- All bolt connections should be checked after driving a short distance when you first install your roof racks.
- All bolted connections should be checked again at regular intervals (weekly is recommended, depending on road conditions, usage, loads and distances travelled).
- All bolted connections should be checked each time they are re-fitted.
- Off-road conditions are more rigorous. Check all bolted connections and your load more regularly.
- Ensure that your vehicle manufacturer's GVM, and gross axle weights are not exceeded (refer to vehicle owner's manual).

Torque Settings:

Unless stated otherwise in these instructions, all fasteners should be set to the following torque settings:




Load Ratings

With the addition of the Batwing Compact Awning, the load capacity of your crossbars will have to be adjusted accordingly. The Batwing Compact Awning with mounting brackets weighs approximately 20kg.

Note for Dealers and Fitters

It is your responsibility to ensure this fitting instruction is given to the end user or client. It is your responsibility to ensure these fitting instructions are given to the end user or client. These instructions remain the property of Rhino-Rack Australia Pty. Ltd. and may not be used or changed for any other purpose than intended.

Critical Dimensions



CONTENTS

Installation onto:

Pioneer Platforms — Steps **1** - **6** and **8** - **15**

HD / RD Crossbars — Steps **7b** - **14** and **16**


VA Crossbars — Steps **7a** , **8** - **14** and **17**

Operation — Steps **18** - **25**

Storage — Steps **26** - **29**

Maintenance & Repair — Page **22** - **23**

Parts List




Item	ASSEMBLED BATWING	Qty	Item	HARDWARE KITS	Qty	Item	PEG BAG	Qty
A	Batwing Main Extrusion	1	L	Base Bracket	2	V	Metal Peg	10
B	Batwing Bag	1	M	M6 x 16 Hex Head Flanged Bolt	4	W	Guy Rope (Blue)	8
C	Batwing End Cap Magnet	4	N	Eye Bolt	1			
D	Batwing Spar Support	4	O	T-Bolt	4			
E	M8 x 150mm Axle Bolt	1	P	Zwifloc Drop-in Nut	5			
F	M8 x 17mm Flat Washer	2	Q	Flat Washer	1			
G	Batwing Spar Hinge Pin	2	R	Torx Key (T30)	1			
H	M8 Nyloc Nut	1	S	M8 Nyloc Nut	4			
I	M6 Nyloc Nut	2	T	M6 x 12 Hex Head Flanged Bolt	4			
J	Hinge Casting	1	U	Square Nut	5			
K	Retention Strap	1						

TOOLS REQUIRED:
T1 - Tape Measure
T2 - 10mm & 13mm Spanner
(or Socket wrench)
T3 - Step Ladder
T4 - Hammer/Mallet
T5 - Phillips Head Screwdriver
T6 - 6mm Allen Key


Bracket Height Setup

The bracket can be set up in **2** different **height configurations**. Before starting, decide which configuration best suits your setup.

(For the purpose of these instructions, the steps are shown in the **LOW** configuration.)



OR





For Installation onto PIONEER PLATFORMS

(For Crossbars, skip to Step **7**)




1

x2





2

x2




3


x2




- 4** Loosely fasten into the channel, but do not tighten.




- 5** Move brackets to outermost edges of Platform, **avoiding channel apertures**.





FOR INSTALLATION ONTO CROSSBARS

(For Platforms skip to Step **8**)






7b



RECONN-DECK CROSSBAR:









i




ii

Once completed, skip to Step **8**



7c

SPORTZ CROSSBAR:**i****ii**

8




9 Ensure the distance between **Bracket** is **no less** than 700mm.




NOTE: Example depicts Pioneer Platforms. Also applies to Cross Bars.

10 Place Awning onto Base Brackets.



NOTE: Step Ladder may be required for taller vehicles.



T3



IMPORTANT:
Inspect both
connections
overhead before
releasing
awning.


NOTE: Example depicts Pioneer Platforms. Also applies to Cross Bars.

- 11** Finger-tighten nuts **S** at all four locations.





NOTE: Example depicts Pioneer Platforms. Also applies to Cross Bars.

- 12** Position Batwing Compact to below dimensions.
NOTE: Be aware of tail gate position and adjust awning accordingly.




- 13** Tighten nuts **S** using **T2** at all four locations.




NOTE: Example depicts Pioneer Platforms. Also applies to Cross Bars.

14





Check fitment is secure



15





NOTE

Eye Bolt will be used as tie-down point for the awning when it is open
 (For **PIONEER** platforms, some flexibility in positioning is possible).



For **RECONN-DECK** , & **SPORTZ**Skip to Step **16**.For **VORTEX BAR** Skip to Step **17**.

Step continues to the next page.

ZWIFLOC™ Lock Guide
UNLOCKED

LOCKED

PIONEER™

16
NOTE

For **crossbar** configurations, use the **Rear bar** on the opposite side of the awning to attach the eyebolt.





Step continues to the next page.

ZWIFLOC™ Lock Guide



UNLOCKED





LOCKED







RECONN-DECK





SPORTZ





17 VORTEX BAR



BATWING COMPACT OPERATION




21



22a Open the **first** Awning wing, and lower pole to the ground.




TWO PEOPLE
REQUIRED




With the help of a second person,
drive pegs through the foot of the
support.



NOTE: Leave a small gap to allow
pegs to be removed easily.



- 22b** Repeat the above process for **Pole 2** and **Pole 3**, then refer to Step **22c**.




- 22c** Repeat the above process for **Pole 4** and **secure all retention straps**.




Ensure 4th support clears the REAR of the vehicle when dropped down.


NOTE: Momentarily undo retention strap when lowering pole if necessary.




23



i





ii

Tighten the strap to achieve a **90°** angle.

24


Tighten the support poles in place at the selected height.

NOTE: Once these heights are set for your vehicle, they can be left at this length even when stowed away.





25

Drive the metal pegs into suitable ground on the outside of the supports. Hook the ropes to the awning, fixing it in place as shown.




NOTE: When raining, lower poles and tension guy rope to help rain flow off awning freely.




STOWAGE INSTRUCTIONS

(Completion of Steps **18** - **25** in REVERSE order. Use below steps for reference)


26 Undo tension strap and all guy ropes.







27a Swing each arm back towards the body of the awning.
Stack each arm **1 - 4** on top of the one before it as shown in **27b**.





27b Place all 4 arms back onto the magnets **C** at the same time.



28

28a Fold the awning material in half.**28b** Roll the material from the front edge back up into its original setting.**28c****29** Replace the metal pegs and guy ropes to their original position. Zip the outer bag closed.

REAR



MAINTENANCE & REPAIR

SUPPORT ARM ADJUSTMENT:

The support arms are designed to allow slight adjustment by the end user. When housed, if the arms are not sitting flush with end cap **Fig. A**, adjust the rotation on the arm using **T5** Phillips Head Screwdriver.







Fig. A: If the arm is off centre, the magnet in the end cap will not secure the arm in place properly.

Fig. B: Loosen the screw behind the drop down hinge, adjust the arm rotation and re-tighten the screw.





HINGE REPAIR:

1. Remove awning from vehicle.
2. Use **T2** 13mm Socket Wrench and **T6** 6mm Allen Key to undo the casting assembly.



3. Remove the assembly pieces & store safely.


4. Using **T5** Phillips Head Screwdriver, remove the screw holding the damaged hinge moulding in place.
5. Replace with the spare hinge provided.




6. Replace the assembly pieces and tighten with **T6** 6mm Allen Key and **T2** 13mm Socket Wrench.

BAG REPLACEMENT:**REMOVAL OF PREVIOUS PVC BAG:**


1. Unzip the bag and remove the velcro straps.



2. Peel bag off the Batwing ends, taking extra care around corners.




3. Carefully slide bag off.


**REPLACEMENT:**

Be sure **correct orientation** is used.
The **matte finish of the PVC bag faces the outside**.


4. Slide new bag into the tracks.



5. Carefully slide bag on.



6. Fold bag over the Batwing ends, taking extra care around corners.





RHINO-RACK®

MAKE SPACE FOR ADVENTURE

RHINORACK.COM

Rhino-Rack AUSTRALIA

22A Hanson Place,
Eastern Creek, NSW 2766

Rhino-Rack USA

19822 E. 22nd Avenue,
Unit B, Aurora, CO 80011