

VEHICLE					PIONEER	CONNECTOR	HEIGHT ADDED mm / in	
SUBARU Crosstrek Gen 3 4WD-SUV Raised Rail 5dr					62100	RX100	80 / 3.1	
REGION	AUS	NZ	USA	CA	SA	UK	EU	ZA
AVAILABILITY	✓	✓	✓	✓	✗	✗	✗	✓
RUN DATES	2023 -	2023 -	2024 -	2024 -	-	-	-	2023 -
VEHICLE NOTES	- Use caution when operating sunroof							

VISIT THE ONLINE CALCULATOR FOR CURRENT SYSTEM LOAD LIMIT DATA



DYNAMIC LOAD LIMIT (ON AND OFF-ROAD):
***USE THE VEHICLE MANUFACTURER'S MAXIMUM ROOF ALLOWANCE IF IT IS LOWER THAN THE FIGURE LISTED**

UP TO **81 Kg**
178 lbs

+

19 Kg
42 lbs

=

UP TO **100 Kg**
220 lbs

OR

***VEHICLE MANUFACTURER'S ROOF LOAD LIMIT**

TOTAL STATIC LOAD LIMIT: UP TO 250 Kg / 551 lbs*

UNDERBAR SPACING

FRONT								REAR
	BAR	A	B	C	D	E	F	
DIMENSION (CM)		-39.4	-1.5	36.4				
SPACERS REQ'D								
CONNECTOR		RX100		RX100				
OUTER UNDERBAR COVER (mm/in)	Refer to Step 11-12 in Pioneer Series 6 Fitting Instructions to trim B and C							
CENTRE UNDERBAR COVER (mm/in)	Refer to Step 11-12 in Pioneer Series 6 Fitting Instructions to trim A							

IF 5-6N/m CANNOT BE OBTAINED

1

8mm Drill Bit

2

5-6Nm
6.5-8LB/FT

3

Plastic Cap M1010

NOTES FOR DEALERS / FITTERS

It is your responsibility to ensure these fitting instructions are given to the end user or client.