



# PIONEER VEHICLE FITTING INFORMATION

CONTROLLED


VEHICLE	PIONEER SIZE	CONNECTOR	HEIGHT ADDED (mm / in)
LAND ROVER Discovery 3/4 L319 4WD/SUV Factory Track 4 dr	52103	RCH6	

## IMPORTANT NOTES

To suit Long Factory Tracks - Do not operate sunroof

REGION	AUS	NZ	USA	CA	SA	UK	EU	ZA
AVAILABILITY	✓	✓	✓	✓	✓	✓	✓	✗
RUNNING DATES	04/05 - 06/17	04/05 - 06/17	2005 -	2005 -	2005 -	2005 - 2017	2005 - 2017	-

## UNDERBAR SPACING



BAR NO.	A	B	C	D	E	F	G
DIMENSION (CM)	-63.1	-30	12.7	38.4	74.5		
SPACERS REQ'D	QMVA10						
CONNECTOR	RCH		RCH		RCH		

VEHICLE LOAD LIMIT (VLL) (kg / lbs)	SYSTEM WEIGHT (SW) (kg / lbs)	ON-ROAD CARGO ALLOW. (OR)	OFF-ROAD CARGO ALLOW. (OFR)
Up to 75 / 165.3 *	32 / 70.5	OR = VLL - SW	OFR = OR / 1.5

\*CHECK YOUR VEHICLE OWNERS HAND BOOK FOR VEHICLE MAXIMUM CARRYING CAPACITY. PLEASE ENSURE YOU USE THE VEHICLE MANUFACTURERS MAXIMUM ROOF ALLOWANCE IF IT IS LOWER THAN THE FIGURE LISTED IN THIS INSTRUCTION.

## NOTES FOR DEALERS / FITTERS

It is your responsibility to ensure these fitting instructions are given to the end user or client.

Document No: R2220  
Issue No: 1  
Issue Date: 14-Apr-20

These instructions remain the property of Rhino-Rack Australia Pty. Ltd. and may not be used or changed for any other purpose than intended.