


| VEHICLE | PIONEER SIZE | CONNECTOR | HEIGHT ADDED (mm / in) |
|--|--------------|-----------|------------------------|
| LEXUS UX Gen 1 4WD/SUV Flush Rail 5 dr | 52109 | SX067 | 110.0 / 4.3 |

IMPORTANT NOTES

- Do not operate sunroof


| REGION | AUS | NZ | USA | CA | SA | UK | EU | ZA |
|---------------|--------|--------|--------|--------|--------|--------|--------|--------|
| AVAILABILITY | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| RUNNING DATES | 2018 - | 2018 - | 2019 - | 2019 - | 2019 - | 2019 - | 2019 - | 2019 - |

UNDERBAR SPACING


| BAR NO. | A | B | C | D | E | F | G |
|----------------|-------|---|-------|---|---|---|---|
| DIMENSION (CM) | -37.5 | 0 | 37.5 | | | | |
| SPACERS REQ'D | | | | | | | |
| CONNECTOR | SX067 | | SX067 | | | | |

| VEHICLE LOAD LIMIT (VLL) (kg / lbs) | SYSTEM WEIGHT (SW) (kg / lbs) | ON-ROAD CARGO ALLOW. (OR) | OFF-ROAD CARGO ALLOW. (OFR) |
|--|----------------------------------|---------------------------|-----------------------------|
| Up to 80 / 176.4 * | 19 / 41.9 | OR = VLL - SW | OFR = OR / 1.5 |

***CHECK YOUR VEHICLE OWNERS HAND BOOK FOR VEHICLE MAXIMUM CARRYING CAPACITY. PLEASE ENSURE YOU USE THE VEHICLE MANUFACTURERS MAXIMUM ROOF ALLOWANCE IF IT IS LOWER THAN THE FIGURE LISTED IN THIS INSTRUCTION.**


NOTES FOR DEALERS / FITTERS

It is your responsibility to ensure these fitting instructions are given to the end user or client.

Document No: R2720
Issue No: 1
Issue Date: 14-Jan-21

These instructions remain the property of Rhino-Rack Australia Pty. Ltd. and may not be used or changed for any other purpose than intended.